


WHAT TO DO WHEN YOUR SPA IS DELIVERED?

Buying a spa is a project in itself and may require some time and thinking from every new spa owner. Here are some **additional specs** and **answers to the common questions** about the **Feeling** spa.



done

electrician.



Place on a solid and well-leveled surface (wooden patio, lawn, rock dust, concrete slab, etc.).



Fill with your garden hose through the skimmer.

COVER LIFTER

The model **#139-Rock-It** is suitable for the Feeling spa and can be ordered from your retailer.

ACCESS

The four sides of the spa are made up of removable panels allowing access to the pump and mechanics.

The spa cover requires a minimal space of 46 cm when opened and slid completely to the side.



* The connection must be

а

certified


by

Cover Opening Direction



The front of the spa is here, when you're facing the keypad!





DIMENSIONS: 215,9 x 180,3 x 86,4 CM

INTERIOR DRAINING VALVE (FRONT)

SPA PACK LOCATED IN FRONT OF THE SPA

PUMP LOCATED IN FRONT OF THE SPA

FILTER CARTRIDGE: #105-0905

FREQUENTLY ASKED QUESTIONS

CAN I INSTALL IT ON MY PATIO?

Yes, if you make sure your structure can withstand the weight of the spa once filled. Make sure your spa cover is safe from the ice falling from your roof.

CAN I PUT IT IN A CORNER?

Yes, only if you retain access to the pump and mechanics via the removable panel. Keep in mind that the spa cover will slide along one side of your spa.

WHAT PRODUCT SHOULD I USE FOR WATER SANITATION ?

Bromine, lithium or biguanide are recommended. The use of chlorine may cancel your warranty

teeling

Having any questions? Send us an email info@purspas.com